

DESCRIPTION


TRAVEL : -5° TO 95° adjustable
 RATIO : 52 : 1
 TURNS TO CLOSE : 13
 WEIGHT : 44.7kg.(98.5lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 125$ [4.92]
 (OFF CENTER) max. $\phi 298$ [11.73]
 acc. ISO 5211 : F12-F14-F16-F25-F30
 BORE : min. $\phi 30$ [1.18] max. $\phi 80$ [3.15] #60 [2.36]

TORQUE

max.OUTPUT : 5500 Nm (48679 lbf.in.)
 max.INPUT : 289 Nm (2562 lbf.in.)
 M.A. : 19 ±15%



rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 1950G LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE FRAME OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE OF THE FOREGOING CONDITIONS



Drawn : N.M
 Dwg Nr.: D06GLB-001

Date : 08-12-08
 Rev.: 01