

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 3.5 kg. 7.7 lb. excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 102$ [4.02]
 acc. ISO 5211 : F05 - F07 - F10
 BORE : min.8.4[0.33] max. $\phi 20$ [0.79] #17

TORQUE

max.OUTPUT : 330 Nm (2920 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%




Dimensions in MM [inch]



Nijverheidstraat 25
 7581 PV Loosdrecht
 The Netherlands

Gearbox AB 210 LX

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M. Date : 07-07-08
 Dwg Nr.: D02LX-010 Rev.: 01

Contents Subject to change without notice.