

**DESCRIPTION**


TRAVEL : -5° to 95° adjustable  
 RATIO : 37 : 1  
 TURNS TO CLOSE : 9.25  
 WEIGHT : 5.5 kg. (12.1lb) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 50$  [1.97]  
 (OFF CENTER) max.  $\phi 125$  [4.92]  
 acc. ISO 5211 : F05-F07-F10-F12  
 BORE : min.10.4[0.41] max. $\phi 30$ [1.18] #24[0.94]

**TORQUE**

max.OUTPUT : 330 Nm (2921 lbf.in.)  
 max.INPUT : 28.5 Nm (252 lbf.in.)  
 M.A. : 11.6  $\pm$ 15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
 72581 PV Losser  
 The Netherlands

# GEARBOX AB 210 N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : S.B.

Date : 04-11-2009

Dwg Nr.: D02N1LB-001

Rev.: 01