


Suitable for insert 07 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 3.5 kg. (7.7 Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 102$ [4.02]
 acc. ISO 5211 : F05-F07-F10
 BORE : min.8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE
 max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 \pm 15%




rotork gears

Nijenheidstraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 210 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE OF THE FOREGOING CONVENTIONS



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D02W1-001

Rev.: 02