


Suitable for insert 07 serie

DESCRIPTION	
TRAVEL	: -5° to 95° adjustable
RATIO	: 37 : 1
TURNS TO CLOSE	: 9.25
WEIGHT	: 3.5 kg. (7.7 Lb) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\phi 50$ [1.97] max. $\phi 102$ [4.02]
acc. ISO 5211	: F05-F07-F10
BORE	: min. $8.4$ [0.33] max. $20$ [0.79] #17[0.67]

TORQUE	
max.OUTPUT	: 500 Nm (4425 lbf.in.)
max.INPUT	: 43 Nm (381 lbf.in.)
M.A.	: 11.6 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
7581 PV Loosdrecht  
The Netherlands

**GEARBOX AB 215 N**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M  
Dwg Nr.: D02NI-011

Date : 22-06-06

Rev.: 02