


Suitable for insert 07 serie

DESCRIPTION	
TRAVEL	: -5° to 95° adjustable
RATIO	: 37 : 1
TURNS TO CLOSE	: 9.25
WEIGHT	: 5.5 kg. (12.1lb) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\phi 50$ [1.97] max. $\phi 125$ [4.92]
acc. ISO 5211	: F05-F07-F10-F12
BORE	: min.8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE	
max.OUTPUT	: 500 Nm (4425 lbf.in.)
max.INPUT	: 43 Nm (381 lbf.in.)
M.A.	: 11.6 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidstroet 25  
7581 PV Losser  
The Netherlands

# GEARBOX AB 215 N LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B. Date : 05-11-2009  
Dwg Nr.: D02N1 LB-011 Rev.: 01