

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 3.5 kg. (7.7 lb) excl. handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\varnothing 50$ [1.97]
 (OFF CENTER) max. $\varnothing 102$ [4.02]
 acc. ISO 5211 : F05-F07-F10
 BORE : min. $\varnothing 10.4$ [0.41] max. $\varnothing 50$ [1.98] #24 [0.94]

TORQUE

max. OUTPUT : 500 Nm (4425 lb.f.in.)
 max. INPUT : 43 Nm (381 lb.f.in.)
 M.A. : 11.6 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenhelderstraat 25
 72581 PV Losser
 The Netherlands

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERNS OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONDITIONS

GEARBOX AB 215 W



Drawn : H.H
 Date : 15-01-04
 Dwg Nr.: D02W-011
 Rev.: 04