

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 8,5 kg.(18.7lb) excludhandwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\varnothing 70$ [2.76]
 (OFF CENTER) : max. $\varnothing 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. 16[0.63] max. $\varnothing 45$ [1.77] #38[1.50]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 550G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLE VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : J.H
 Date : 07-03-02
 Dwg Nr.: D03G-001
 Rev.: 06