

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 8,5 kg.(18.7 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. $\phi 10.63$ max. $\phi 30$ [1.18] #27 [1.06]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 550 LX

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESS VALUE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE PREVIOUS CONDITIONS



Drawn : H.L

Date : JAN. 2000

Dwg Nr.: D03X-001

Rev.: 05