


Suitable for insert 10 serie

DESCRIPTION	
TRAVEL	: -5 TO 95° adjustable
RATIO	: 34 : 1
TURNS TO CLOSE	: 8.5
WEIGHT	: 8,5 kg.(18.7Lb) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\varnothing 70$ [2.76] max. $\varnothing 140$ [5.51]
acc. ISO 5211	: F07-F10-F12-F14
BORE	: min.16[0.63] max. $\varnothing 30$ [1.18]#27[1.06]

TORQUE	
max.OUTPUT	: 1000 Nm (8851 lbf.in.)
max.INPUT	: 83 Nm (738 lbf.in.)
M.A.	: 12.0 \pm 15%



Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
7581 PV Loosdrecht
The Netherlands

GEARBOX AB 550N

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. FOR MORE INFORMATION, PLEASE CONTACT THE SALES DEPARTMENT OR THE TECHNICAL SUPPORT DEPARTMENT.



Drawn : N.M
Dwg Nr.: D03NI-001

Date : 22-06-06
Rev.: 01