


Suitable for insert 10 serie

**DESCRIPTION**  
 TRAVEL : -5 TO 95° adjustable  
 RATIO : 34 : 1  
 TURNS TO CLOSE : 8.5  
 WEIGHT : 11,5 kg.(25.3lb) excl.handwheel

**MOUNTINGHOLES**  
 BOLT CIRCLE : min.  $\varnothing 70$  [2.76]  
 (OFF CENTER) max.  $\varnothing 165$  [6.50]  
 acc. ISO 5211 : F07-F10-F12-F14-F16  
 BORE : min.16[0.63] max.  $\varnothing 30$ [1.18]#27[1.06]

**TORQUE**  
 max.OUTPUT : 1000 Nm (8851 lbf.in.)  
 max.INPUT : 83 Nm (738 lbf.in.)  
 M.A. : 12.0  $\pm$ 15%




Dimensions in MM [inch]

**rotork gears**

Nijverheidstroet 25  
 72581 PV Losser  
 The Netherlands

**GEARBOX AB 550N LB**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE AND/OR TRADE SECRET OF ROTORK GEARS.



Drawn : N.M  
 Date : 10-03-2010  
 Dwg Nr.: D03NILB-001  
 Rev.: 02

Contents Subject to change without notice.