

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 8,5 kg.(18,7Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\varnothing 70$ [2.76]
 (OFF CENTER) max. $\varnothing 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min.16[0.63] max.45[1.77] #38[1.50]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 550W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE AKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 07-03-02

Dwg Nr.: D03W-001

Rev.: 06