

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11,5 kg.(25.3Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\varnothing 70$ [2.76]
 (OFF CENTER) max. $\varnothing 165$ [6.50]
 acc. ISO 5211 : F07-F10-F12-F14-F16
 BORE : min.16[0.63] max.45[1.77] #38[1.50]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 550W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : N.M.
 Date : 10-03-2010
 Dwg Nr.: D03WLB-001
 Rev.: 02