

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 78 : 1  
 TURNS TO CLOSE : 19,5  
 WEIGHT : 86,9kg.(192Lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 165$  [6.50]  
 (OFF CENTER) max.  $\phi 356$  [14.02]  
 acc. ISO 5211 : F16-F25-F30-F35  
 BORE : min.30[1.18] max. $\phi 100$ [3.94] #75[2.95]

**TORQUE**

max.OUTPUT : 8400 Nm (74364 lbf.in.)  
 max.INPUT : 305 Nm (2704 lbf.in.)  
 M.A. : 27,5 ±15%




**rotork gears**

Nijverheidestraat 25  
 7581 PV Losser  
 The Netherlands

**GEARBOX AB 6800G LB**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : N.M.  
 Dwg Nr.: D08GLB-001

Date : 08-12-08  
 Rev.: 01