

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 86,9kg.(192lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 165$ [6.50]
 (OFF CENTER) max. $\phi 356$ [14.02]
 acc. ISO 5211 : F16-F25-F30-F35
 BORE : min.30[1.18]max. $\phi 100$ [3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74346 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 6800W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ANY RE-USE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLE VIOLATION OF THE AGREEMENT CONDITIONS



Drawn : N.M.

Date : 09-12-08

Dwg Nr.: D08WLB-001

Rev.: 01