


Suitable for insert 150 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 14 kg. (31 Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 165$ [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min. $\phi 10.63$ max. $\phi 44$ [1.73] #36 [1.42]

TORQUE
 max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 880 G

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS AND TRADE MARKS OF ROTORK GEARS.



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D04G1-001

Rev.: 01