

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 17 kg. (37.5Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 220 [8.66] 8x M16
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min. ϕ 60 [2.36] #46 [1.81]

TORQUE

max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 \pm 15%



Dimensions in MM [inch]

rotork gears

Nijenheldestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 880 G LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : S.B. Date : 05-11-2009
 Dwg Nr.: D04GLB-001 Rev.: 01