

DESCRIPTION


Travel : -5° to 95° adjustment
 Ratio : 38 : 1
 Turns to Close : 95
 Weight : 14 Kg. (31 Lb.) Excl. Handwheel

MOUNTINGHOLES

Bolt Circle : Min. \varnothing 102 [4.02]
 (Off Center) Max. \varnothing 165 [6.5]
 Acc. ISO 5211 : F10 - F12 - F14 - F16
 Bore : Min. \varnothing 16 [0.63] - Max. \varnothing 44 [1.73] # 36

TORQUE


Max. Output : 1620 Nm (14350 lbf. in.)
 Max. Input : 123 Nm (1089 lbf. in.)
 M.A. : 13.2 ± 15%



Nijverheidstraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 880 LX

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGMENT OF THE FOREGOING CONDITIONS



Drawn : N.M. Date : 07-07-08

Dwg Nr.: D04LX-010 Rev.: 01

Contents Subject to change without notice.