

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 14 kg. (31 Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 165 [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min.16[0.63] max. ϕ 60[2.36] #46[1.81]

TORQUE

max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 \pm 15%




rotork gears

Nijenhelderstraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 880 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : H.L

Date : JAN. 2000

Dwg Nr.: D04W-001

Rev.: 07