

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 17 kg. (37.5Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 220 [8.66] 8x M16
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min.16[0.63] max. ϕ 60[2.36] #46[1.81]

TORQUE

max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7281 PV Losser
 The Netherlands

GEARBOX AB 880 W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. RETURN TO THE INTEREST OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGE OF THE PERSONS IN CONDITIONS



Drawn : S.B. Date : 05-11-2009
 Dwg Nr.: D04WLB-001 Rev.: 01