


Suitable for insert 150 serie

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 17 kg. (37.5Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 220$ [8.66] 8x M16
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min. $\phi 63$ max. $\phi 45$ [1.77] #36 [1.42]

TORQUE
 max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 $\pm 15\%$




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 880 W LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY. PERMISSION TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE PERSONS CONDITIONS



Drawn : S.B.
 Dwg Nr.: D04WLB-001

Date : 05-11-2009
 Rev.: 01