

Suitable for 150 series insert

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 55 : 1  
 TURNS TO CLOSE : 13.75  
 WEIGHT : 22 kg.(48.5 lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 102$  [4.02]  
 (OFF CENTER) max.  $\phi 165$  [6.50]  
 acc. ISO 5211 : F10-F12-F14-F16  
 BORE : min. $\phi 16$ [0.63] max. $\phi 45$ [1.77] #36[1.42]

**TORQUE**

max.OUTPUT : 3250 Nm (28765 lbf.in.)  
 max.INPUT : 171 Nm (1514 lbf.in.)  
 M.A. : 19 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijverheidstraat 25  
 7581 Lely Loosdrecht  
 The Netherlands

# GEARBOX E 1250G F10 BU L

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg N°: E 1250G F10 BU L

Rev.: 01

Contents Subject to change without notice.