


Suitable for insert 07 serie

DESCRIPTION	
TRAVEL	: 90° ±5° AT BOTH ENDS.
RATIO	: 37 : 1
TURNS TO CLOSE	: 9.25
WEIGHT	: 4 kg.(8.8 lb.) excl.handwheel

MOUNTINGHOLES	
BOLT CIRCLE (OFF CENTER)	: min. $\phi 50$ [1.97] max. $\phi 102$ [4.02]
ecc. ISO 5211	: F05 - F07 - F10
BORE	: min.8.4[0.33] max. $\phi 20$ [0.79] #17[0.67]

TORQUE	
max.OUTPUT	: 330 Nm (2921 lbf.in.)
max.INPUT	: 28.5 (252 lbf.in.)
M.A.	: 11.6 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidstroet 25
7581 PV Loosdrecht
The Netherlands

GEARBOX E 210 G / F10

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : N.M

Date : 22-06-06

Dwg Nr.: D15G1-003

Rev.: 01