

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 4 kg.(8.8 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 50$ [1.97]
 (OFF CENTER) max. $\phi 102$ [4.02]
 acc. ISO 5211 : F05 - F07 - F10
 BORE : min.8.4[0.33] max. $\phi 30$ [1.18] #24[0.94]

TORQUE

max.OUTPUT : 500 Nm (4425 lbf.in.)
 max.INPUT : 43 Nm (381 lbf.in.)
 M.A. : 11.6 ±15%



Dimensions in MM [Inch]

rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX E 215G F10 BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. ANY PART OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: E 215G F10 BUL

Rev.: 01