


Suitable for insert 10 serie

DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11 kg.(24.3 lb.) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\varnothing 70$ [2.76]
 (OFF CENTER) max. $\varnothing 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min.16[0.63] max.30[1.18] #27[1.06]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%




rotork gears

Nijverheidstroet 25
 7281 PV Losser
 The Netherlands

GEARBOX E 550G F10 BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE EXPRESS WRITTEN PERMISSION OF ROTORK GEARS. IN THE INTEREST OF ROTORK GEARS, ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A SIGNIFICANT INVESTMENT ON THE PERSONS CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: E 550GI F10 BUL

Rev.: 01