

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 11 kg.(24.3 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. $\phi 45$ [1.77] #38 [1.50]

TORQUE

max.OUTPUT : 1000 Nm (885 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 ±15%




rotork gears

Nijenheldestraat 25
 7281 PV Losser
 The Netherlands

GEARBOX E 550G F10 BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. IN THE INTEREST OF ROTORK GEARS, ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: E 550G F10 BUL

Rev.: 01