



RATIO	M.A.	C.O.G.			MAX OUTPUT TORQUE Nm (lbs-ft)
		X	Y	Z	
3	2.55	0	46	38	2033 (1500)
4	3.40	0	50	37	2033 (1500)
6	5.10	0	50	36	1627 (1200)

MAX BORE SQ KEY			MAX BORE RECTANGULAR KEY			MAX STEM SCREW ACCEPTANCE DIA.
STD	BORE	KEY	STD	BORE	KEY	
BS4235	-	-	BS4235	76.0	22X14	86(3.375")
BS46	2.750"	3/4" SQ	BS46	3.000"	3/4"X1/2"	
ANSI B17.1	2.750"	5/8" SQ	ANSI B17.1	3.000"	3/4"X1/2"	

	INPUT FLANGE DETAILS					BASEPLATE DETAILS	
	FLANGE O/DIA. & THICKNESS	SHAFT DIA.	RECESS DIA.	RECESS DEPTH	HOLE DETAILS 45°(OFF CENTRES)	SPIGOT DIA.	HOLE DETAILS (22.5° OFF CENTRES)
ISO F14	Ø175 x 15 (Ø6.89" x 0.59")	Ø30.00-0.05 (Ø1.181"-0.002")	Ø100.05+0.05 (Ø3.939"+0.002")	5 (0.20")	4 HOLES Ø16.5 (Ø0.65")	Ø199.95-0.05 (Ø7.872"-0.002")	8 HOLES M16X20 (0.79") DEEP ON Ø254.0 (Ø10.00") P.C.
	Ø175 x 15 (Ø6.89" x 0.59")	Ø30.00-0.05 (Ø1.181"-0.002")	Ø95.27+0.05 (Ø3.751"+0.002")	5 (0.20")	4 HOLES Ø16.5 (Ø0.65")	Ø152.25-0.05 (Ø5.994"-0.002")	8 HOLES 5/8"UNCX20 (0.79") DEEP ON Ø254.4 (Ø10.00") P.C.
FA14	Ø175 x 15 (Ø6.89" x 0.59")	Ø30.00-0.05 (Ø1.181"-0.002")	Ø95.27+0.05 (Ø3.751"+0.002")	5 (0.20")	4 HOLES Ø16.5 (Ø0.65")	Ø152.25-0.05 (Ø5.994"-0.002")	8 HOLES 5/8"UNCX20 (0.79") DEEP ON Ø254.4 (Ø10.00") P.C.

**rotork
gears**

IB9 GEARBOX
F14/FA14 INPUT F25/FA25 OUTPUT

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com

APPROX WEIGHT 62.0 kg

DRAWING No	PUBIB9-F14-F25	Regina House Ring Road Bramley Leeds LS134ET United Kingdom
ISSUE	01	
DATE	09/05/2011	