

**DESCRIPTION**


TRAVEL : -5° to 95° adjustable  
 RATIO : 55 : 1  
 TURNS TO CLOSE : 13.75  
 WEIGHT : 22 kg. (48 Lb) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 102 [4.02]$   
 (OFF CENTER) max.  $\phi 165 [6.50]$   
 acc. ISO 5211 : F10-F12-F14-F16  
 BORE : min.  $20[0.79]$  max.  $\phi 65[2.56]$  #50[1.97]

**TORQUE**

max.OUTPUT : 3250 Nm (28675 lbf.in.)  
 max.INPUT : 171 Nm (1514 lbf.in.)  
 M.A. : 19 ±15%



Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
 7581 PV Loosdrecht  
 The Netherlands

# GEARBOX AB 1250 CS

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERNS OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : B.H

Date : 18-07-2011

Dwg Nr.: D05CS-001

Rev.: 00