

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 27.5kg. (60.6Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 102 [4.02]
 (OFF CENTER) max. ϕ 254 [10]
 acc. ISO 5211 : F10/12/14/16/25
 BORE : min.20[0.79] max. ϕ 65[2.56] #50[1.97]

TORQUE

max.OUTPUT : 3250 Nm (28675 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 \pm 15%




rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 1250 G BU LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ABOVE FINISH OF THIS DOCUMENT SHALL CONSTITUTE A SIGNIFICANT DEVIATION OF THE FOREGOING CONDITIONS



Drawn : S.B.

Date : 06-11-2009

Dwg Nr.: AB 1250G LB BU L

Rev.: 01