

DESCRIPTION


TRAVEL : -5° TO 95° adjustable
 RATIO : 52 : 1
 TURNS TO CLOSE : 13
 WEIGHT : 32,5kg.(72 Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. ϕ 125 [4.92]
 (OFF CENTER) max. ϕ 254 [10.00]
 acc. ISO 5211 : F12-F14-F16-F25
 BORE : min.30[1.18] max.80[3.15] #60[2.36]

TORQUE

max.OUTPUT : 5500 Nm (48679 lbf.in.)
 max.INPUT : 289 Nm (2562 lbf.in.)
 M.A. : 19 ±15%




rotork gears

Nijenhelderstraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 1950 G BU

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ABOVE FINANCE OF THIS DOCUMENT SHALL CONSTITUTE A FORMAL REQUISITION OF THE FOREGOING CONDITIONS



Drawn : P.VH

Date : 28-01-09

Dwg Nr.: AB1950 G BU L

Rev.: 01