

**DESCRIPTION**


TRAVEL : -5° to 95° adjustable  
 RATIO : 37 : 1  
 TURNS TO CLOSE : 9.25  
 WEIGHT : 4 Kg. (8.8 Lb.) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 50 [1.97]$   
 (OFF CENTER) max.  $\phi 102 [4.02]$   
 dec. ISO 5211 : F05-F07-F10  
 BORE : min.10.4[0.41] max.  $\phi 30 [1.18]$  #24[0.94]

**TORQUE**

max.OUTPUT : 330 Nm (2921 lbf.in.)  
 max.INPUT : 28.5 Nm (252 lbf.in.)  
 M.A. : 11.6 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
 72581 PV Losser  
 The Netherlands

**GEARBOX AB 210G BUL**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERESTS OF ROTORK GEARS. ASSESSOR OF THIS DOCUMENT SHALL CONSULT THE KNOWLEDGEABLES OF THE PERSONS IN CONNECTIONS



Drawn : P.VH  
 Date : 28-01-09  
 Dwg Nr.: AB 210 G BUL  
 Rev.: 01