

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5.5kg, (12.1lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. Ø50 [1.97]
 (OFF CENTER) max. Ø125 [4.92]
 ecc. ISO 5211 : F05-F07-F10-F12
 BORE : min.10.4[0.41] max.Ø30[1.18] #24[0.94]

TORQUE

max.OUTPUT : 330 Nm (2921 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%




rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX AB 210G LB BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED BY THE INTERNS OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLEMENT OF THE FOREGOING CONDITIONS



Drawn : S.B.

Date : 05-11-2009

Dwg Nr.: AB 210 G LB BUL

Rev.: 01