

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 8,5 kg.(18.7lb) excludhandwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min. $\phi 16$ [0.63] max. $\phi 45$ [1.77] #38[1.50]

TORQUE

max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ABOVE FINDE OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEMENT OF THE PERSONS IN CONVICTIONS

GEARBOX AB 550G BUL



Drawn : P.VH
 Date : 28-01-09
 Dwg Nr.: AB 550G BUL
 Rev.: 01