

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 78 : 1
 TURNS TO CLOSE : 19,5
 WEIGHT : 56,5kg.(125Lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 165$ [6.50]
 (OFF CENTER) max. $\phi 298$ [11.73]
 acc. ISO 5211 : F16-F25-F30
 BORE : min. $\phi 100$ [3.94] max. $\phi 100$ [3.94] #75[2.95]

TORQUE

max.OUTPUT : 8400 Nm (74364 lbf.in.)
 max.INPUT : 305 Nm (2704 lbf.in.)
 M.A. : 27,5 ±15%



rotork gears

Nijenheidestraat 25
 72581 PV Losser
 The Netherlands

GEARBOX AB 6800 CS

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLE VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.



Drawn : B.H
 Dwg Nr.: D08CS-001

Date : 18-07-2011
 Rev.: 00