

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 14 kg. (31 Lb) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 165$ [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min. $16[0.63]$ max. $\phi 60[2.36]$ #46[1.81]

TORQUE

max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 72581 PV Loozer
 The Netherlands

GEARBOX AB 880 CS

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ANYONE WHOSE NAME OF THIS DOCUMENT SHALL CONSTITUTE AKNOWLEDGEMENT OF THE PERSONS CONDITIONS



Drawn : B.H
 Dwg Nr.: D04CS-001

Date : 18-07-2011
 Rev.: 00