

**DESCRIPTION**


TRAVEL : -5° to 95° adjustable  
 RATIO : 38 : 1  
 TURNS TO CLOSE : 9,5  
 WEIGHT : 14 kg. (31 Lb) excl.handwheel

**MOUNTINGHOLES**

BOLT CIRCLE : min.  $\phi 102$  [4.02]  
 (OFF CENTER) max.  $\phi 165$  [6.50]  
 acc. ISO 5211 : F10-F12-F14-F16  
 BORE : min.  $16[0.63]$  max.  $60[2.36]$  #46[1.81]

**TORQUE**

max.OUTPUT : 2000 Nm (17701 lbf.in.)  
 max.INPUT : 152 Nm (1341 lbf.in.)  
 M.A. : 13.2  $\pm$ 15%




Dimensions in MM [inch]

**rotork gears**

Nijenheidestraat 25  
 72581 PV Losser  
 The Netherlands

# GEARBOX AB 880G BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A BREACH OF THE PERSONAL CONDITIONS



Drawn : P.VH

Dwg Nr.: AB 880G BUL

Rev.: 01

Date : 28-01-09