

DESCRIPTION


TRAVEL : -5° to 95° adjustable
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 14 kg.(31 lb.) excl.handwheel

MOUNTINGHOLES

BOLT CIRCLE : min. Ø102 [4.02]
 (OFF CENTER) max. Ø165 [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min.16[0.63] max.Ø60[2.36] #46[1.81]

TORQUE

max.OUTPUT : 2000 Nm (17701 lbf.in.)
 max.INPUT : 152 Nm (1341 lbf.in.)
 M.A. : 13.2 ±15%




Dimensions in MM [inch]

rotork gears

Nijenhelderstraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX E 880G F10 BUL

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY PERMITTED TO THE INTEREST OF ROTORK GEARS. ASSESSMENT OF THIS DOCUMENT SHALL CONSTITUTE AWARENESS OF THE APPLICABLE CONDITIONS



Drawn : P.VH Date : 28-01-09

Dwg Nr.: E 880G F10 BUL Rev.: 01