

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 592 : 1  
 TURNS TO CLOSE : 148  
 WEIGHT : 157kg. (346lb.) excl.handwheel

**MOUNTINGHOLES**

Valve connection : F25/F30/F35  
 MAX. bore :  $\varnothing$  90 [3.54] or  $\varnothing$  130 [5.12]  
 Actuator connection : F25/F30/F35  
 MAX. shaft :  $\varnothing$  100[3.94] or  $\varnothing$  150[5.91]

**TORQUE**

max.OUTPUT :26000Nm (230119 lbf.in.)  
 max.INPUT : 166 Nm (1466 lbf.in.)  
 M.A. : 157 ±15%



**rotork gears**

Nijverheidstraat 25  
 7561 LA, Loosdrecht  
 The Netherlands

**GEARBOX ILG/S200-SP9**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.

Date : 16-06-10

Dwg Nr.: D27ILGS-002

Rev.: 00

Contents Subject to change without notice.