

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 37 : 1  
 TURNS TO CLOSE : 9.25  
 WEIGHT : 7 kg.(15.4lb.) excl.handwheel

**MOUNTING DIMENSIONS**

Valve connection : F05/F07/F10/F12  
 MAX. bore :  $\varnothing 17$  [0.67] or  $\varnothing 20$  [0.79]  
 Actuator connection : F05/F07/F10  
 MAX. shaft :  $\varnothing 19$  [0.75] or  $\varnothing 24$  [0.94]

**TORQUE**

max.OUTPUT : 330 Nm (2920 lbf.in.)  
 max.INPUT : 28.5 Nm (252 lbf.in.)  
 M.A. : 11.6 ±15%




Dimensions in MM [inch]

**rotork gears**

Nijverheidstraat 25  
 7361 PV, Loosdrecht  
 The Netherlands

# GEARBOX ILG/S 210 LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : j.t.p  
 Dwg Nr.: D30N1LB-001  
 Date : 08-06-10  
 Rev.: 00

Contents Subject to change without notice.