

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 34 : 1  
 TURNS TO CLOSE : 8.5  
 WEIGHT : 13 kg.(28.5 lb.)excl.handwheel

**MOUNTING DIMENSIONS**

Valve connection:F07/F10/F12/F14/F16  
 MAX. bore :  $\phi$ 27 [1.06] or  $\phi$ 32 [1.26]  
 Actuator connection : F07/F10/F12  
 MAX. shaft :  $\phi$ 27 [1.06] or  $\phi$ 36 [1.42]

**TORQUE**

max.OUTPUT : 934 Nm (8270 lbf.in.)  
 max.INPUT : 78 Nm (688 lbf.in.)  
 M.A. : 12.0 ±15%




**rotork gears**

Nijverheidstraat 25  
 7561 Lelystad  
 The Netherlands

**GEARBOX ILG/S 550 LB**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS, ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.t.P.  
 Dwg Nr.: D31N1LB-001

Date : 08-06-10  
 Rev.: 00

Contents Subject to change without notice.