

DESCRIPTION


TRAVEL : 90° $\pm 5^\circ$ AT BOTH ENDS.
 RATIO : 220 : 1
 TURNS TO CLOSE : 55
 WEIGHT : 37 kg.(81.5 lb.) excl.handwheel

MOUNTING DIMENSIONS

Valve connection : F10/F12/F14/F16
 MAX. bore : $\phi 36$ [1.42] or $\phi 45$ [1.77]
 Actuator connection : F12/F14/F16
 MAX. shaft : $\phi 46$ [1.81] or $\phi 60$ [2.36]

TORQUE

max.OUTPUT : 2640 Nm (23380 lbf.in.)
 max.INPUT : 66 Nm (585 lbf.in.)
 M.A. : 40 $\pm 15\%$




rotork gears

Nijenheidestraat 25
 7581 PV Losser
 The Netherlands

GEARBOX ILG/S 1250-SP4

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.
 Date : 05-01-'11
 Dwg Nr.: D33NSP4-001
 Rev.: 00