

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 78 : 1  
 TURNS TO CLOSE : 19,5  
 WEIGHT : 70kg.(154lb.) excl.handwheel

**MOUNTING DIMENSIONS**

Valve connection : F16/F25/F30  
 MAX. bore :  $\phi 55,0$  [2.17] or  $\phi 70$  [2.76]  
 Actuator connection : F25/F30  
 MAX. shaft :  $\phi 75$  [2.95] or  $\phi 100$  [3.94]

**TORQUE**

max. OUTPUT : 8400 Nm (74346 lbf.in.)  
 max. INPUT : 305 Nm (2704 lbf.in.)  
 M.A. : 27,5 ±15%




**rotork gears**

Nijverheidstraat 25  
 7561 N Losser  
 The Netherlands

**GEARBOX ILG/S 6800**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.

Date : JAN. 2007

Dwg Nr.: D361N-0000

Rev.: 01

Contents Subject to change without notice.