

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 480 : 1
 TURNS TO CLOSE : 120
 WEIGHT : 125.4kg.(276lb.) excl.handwheel

MOUNTING DIMENSIONS

Valve connection : F16/F25/F30
 MAX. bore : \varnothing 55 [2.17] or \varnothing 65 [2.56]
 Actuator connection : F25/F30
 MAX. shaft : \varnothing 75 [2.95] or \varnothing 100 [3.94]

TORQUE

max.OUTPUT : 17000 Nm (150620lbf.in.)
 max.INPUT : 108 Nm (958 lbf.in.)
 M.A. : 157 ±15%




rotork gears

Nijverheidswaag 25
 The Netherlands

GEARBOX ILG/S 6800 SP6 LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M. Date : June 2010
 Dwg Nf.: D68NLB-003 Rev.: 01