

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 480 : 1
 TURNS TO CLOSE : 120
 WEIGHT : 95kg. (209 Lb.)excl.handwheel

MOUNTING DIMENSIONS

Valve connection : F16/F25/F30
 MAX. bore : \varnothing 55 [2.17] or \varnothing 65 [2.56]
 Actuator connection : F25/F30
 MAX. shaft : \varnothing 75 [2.95] or \varnothing 100 [3.94]

TORQUE

max.OUTPUT : 17000 Nm (150620lbf.in.)
 max.INPUT : 108 Nm (958 lbf.in.)
 M.A. : 157 ±15%




rotork gears

Nijverheidstraat 25
 7561 NLY, Loosdrecht
 The Netherlands

GEARBOX ILG/S 6800 SP6

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS, ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.
 Dwg Nf.: D68N-003

Date : June 2010
 Rev.: 01