


DESCRIPTION
 RATIO : 34 : 1
 WEIGHT : 8,5 kg (18.7Lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 70$ [2.76]
 (OFF CENTER) max. $\phi 140$ [5.51]
 acc. ISO 5211 : F07-F10-F12-F14
 BORE : min.16[0.63] max.45[1.77] #38[1.50]

TORQUE
 max.OUTPUT : 1000 Nm (8851 lbf.in.)
 max.INPUT : 83 Nm (738 lbf.in.)
 M.A. : 12.0 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenhelderstraat 25
 72581 PV Loosdrecht
 The Netherlands

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A VIOLATION OF THE PATENT RIGHTS OF ROTORK GEARS.

GEARBOX AB 550N 360°



Drawn : R.K

Date : 17-10-03

Dwg Nr.: AB 550N 360°

Rev.: 03