


Suitable for 150 series insert

DESCRIPTION
 TRAVEL : -5° to 95° adjustable
 RATIO : 55 : 1
 TURNS TO CLOSE : 13.75
 WEIGHT : 22kg. (48.5lb) excl.handwheel

MOUNTINGHOLES
 BOLT CIRCLE : min. $\phi 102$ [4.02]
 (OFF CENTER) max. $\phi 165$ [6.50]
 acc. ISO 5211 : F10-F12-F14-F16
 BORE : min. $\phi 16$ [0.63] max. $\phi 44$ [1.77] #36[1.42]

TORQUE
 max.OUTPUT : 3250 Nm (28765 lbf.in.)
 max.INPUT : 171 Nm (1514 lbf.in.)
 M.A. : 19 \pm 15%




Dimensions in MM [inch]

rotork gears

Nijenheidestraat 25
 7581 PV Loosdrecht
 The Netherlands

GEARBOX AB 1250 W

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN CONSENT OF ROTORK GEARS. ANY REPRODUCTION OF THIS DOCUMENT SHALL CONSTITUTE A KNOWLEDGEABLE VIOLATION OF THE APPLICABLE CONDITIONS



Drawn : N.M

Date : 20-06-06

Dwg Nr.: D05W1-001

Rev.: 01