

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 37 : 1
 TURNS TO CLOSE : 9.25
 WEIGHT : 5 kg.(11 lb.) excl.handwheel

MOUNTING DIMENSIONS

Valve connection : F05/F07/F10
 MAX. bore : $\phi 17$ [0.67] or $\phi 20$ [0.79]
 Actuator connection : F05/F07/F10
 MAX. shaft : $\phi 19$ [0.75] or $\phi 24$ [0.94]

TORQUE

max.OUTPUT : 330 Nm (2920 lbf.in.)
 max.INPUT : 28.5 Nm (252 lbf.in.)
 M.A. : 11.6 ±15%




rotork gears

Nijverheidstraat 25
 7361 PV, Loosdrecht
 The Netherlands

GEARBOX ILG/S 210

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 18-03-02

Dwg Nr.: D30N-001

Rev.: 06

Contents Subject to change without notice.