

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 707 : 1
 TURNS TO CLOSE : 176.75
 WEIGHT : 235 kg.(518 lb.) excl.handwheel

MOUNTINGHOLES

Valve connection : F25/F30/F35/F40
 MAX. bore : \varnothing 90 [3.54] or \varnothing 130 [5.12]
 Actuator connection : F25/F30/F35
 MAX. shaft : \varnothing 100[3.94] or \varnothing 150[5.91]

TORQUE

max.OUTPUT : 32000 Nm (283200 lbf.in.)
 max.INPUT : 142 Nm (1259 lbf.in.)
 M.A. : 225 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidsweg 25
 7561 N Loosdrecht
 The Netherlands

GEARBOX ILG/S 250 - SP9

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS, NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE INTEREST OF ROTORK GEARS, ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 18-03-02

Dwg Nr.: D37N-001

Rev.: 07

Contents Subject to change without notice.