


DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 34 : 1
 TURNS TO CLOSE : 8,5
 WEIGHT : 10 kg.(22 lb.) excl.handwheel

MOUNTING DIMENSIONS
 Valve connection : F07/F10/F12/F14
 MAX. bore : ϕ 27 [1.06] or ϕ 32 [1.26]
 Actuator connection : F07/F10/F12
 MAX. shaft : ϕ 27 [1.06] or ϕ 36 [1.42]

TORQUE
 max.OUTPUT : 934 Nm (8270 lbf.in.)
 max.INPUT : 78 Nm (688 lbf.in.)
 M.A. : 12.0 ±15%




Dimensions in MM [inch]



Nijverheidsweg 25
 7561 LA, Loosdrecht
 The Netherlands

GEARBOX ILG/S 550

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H
 Dwg Nr.: D31N-001

Date : 18-03-02
 Rev.: 06

Contents Subject to change without notice.