


DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 55 : 1
 TURNS TO CLOSE : 13,75
 WEIGHT : 22 kg.(48.5 lb.) excl.handwheel

MOUNTING DIMENSIONS
 Valve connection : F10/F12/F14/F16
 MAX. bore : \varnothing 36 [1.42] or \varnothing 45 [1.77]
 Actuator connection : F12/F14/F16
 MAX. shaft : \varnothing 46 [1.81] or \varnothing 60 [2.36]

TORQUE
 max.OUTPUT : 2640 Nm (23380 lbf.in.)
 max.INPUT : 139 Nm (1230 lbf.in.)
 M.A. : 19 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidsweg 25
 7561 Nieuw-Losser
 The Netherlands

GEARBOX ILG/S 1250

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 18-03-02

Dwg Nr.: D33N-001

Rev.: 06

Contents Subject to change without notice.